







E-Star Power Development Co., Ltd. (E-STAR)
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City
 22069, Taiwan (R.O.C.)
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

18W Wall Mount interchangeable Medical power supply > GMPU18


UNIT:mm




AC Plug-US




AC Plug-EU




AC Plug-SA




AC Plug-UK




AC Plug-CH



AC Plug-KR



AC Plug-AR



AC Plug-JP

■ Safety agency approvals:



■ Specifications:

Model No.	GMPU18
AC input range	100~240VAC; 47~63Hz; 0.45~0.2A
Leakage current	0.1mA Max.@ 240VAC/50Hz
Operating temperature	-20°C to~ +70°C(safety approval 0°C to 40°C, >40°C please contact the sales request derating curve.)
Withstand voltage	5656VDC from input to output
EMC	(A)CE:EN60601-1-2 (B)FCC Part 15 / Part 18 CLASS B
Safety	(A)UL/cUL (B)TUV/GS (C) TUV/PSE (D)CB
Warranty	2 years

■ **X = UI:** (American type_FIG 1) or **EI:** (European type_FIG 2) or **SAI:** (2pin Australian type_FIG3) or **BSI:** (British type_FIG 4) or **CHI:** (Chinese type_FIG 5) or **KRI:** (Korean type_FIG 6) or **ARI:** (Argentinian type_FIG 7) or or **JPI:** (Japanese type_FIG 8)

Model name	Output Voltage(VDC)	Output Current(A)	Max.Output power(W)	Ripple.(mV) max.	Line Regulation(%)	Load Regulation(%)	Avg.Eff.(%) DoE(VI)_CoC(5)	No load Power Consumption(W)	Measured at the output of
GMPU18X-1	5~6	3.00~2.50	15	80	±1	±5	>81.39	<0.1	5
GMPU18X-1-1	6~8	2.50~1.87	15	80	±1	±5	>84.13	<0.1	7.5
GMPU18X-2	8~11	2.25~1.64	18.04	100	±1	±5	>85	<0.1	9
GMPU18X-3	11~13	1.64~1.38	18.04	120	±1	±3	>85	<0.1	12
GMPU18X-4	13~16	1.38~1.13	18.08	150	±1	±3	>85	<0.1	15
GMPU18X-5	16~21	1.13~0.86	18.08	150	±1	±2	>85	<0.1	18
GMPU18X-6	21~27	0.86~0.67	18.09	150	±1	±2	>85	<0.1	24
GMPU18X-7	27~33	0.67~0.55	18.15	240	±1	±3	>85	<0.1	28
GMPU18X-8	33~58	0.55~0.32	18.56	240	±1	±2	>85	<0.1	48

Note:

- 1.Weight: Approx 140~160gs
- 2.Optional output connectors (See appendix A)
- 3.Avg. Eff.(%): Averages the efficiency at 25, 50, 75, and 100 % of max. rated output current
- 4.Standard Output cable: **5~11V:** UL2468, 16AWG, 1M ; **11~13V:** UL2468, 18AWG, 1M ; **13~58V:** UL2468, 22AWG, 5FT