



E-Star Power Development Co., Ltd. (E-STAR)
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City
 22069, Taiwan (R.O.C.)
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

40W Wall Mount interchangeable Medical power supply > GMPU40



FIG 1: American Type



FIG 2: European Type



FIG 3: Australian Type



FIG 4: British Type



FIG 5: Chinese Type






FIG 6: Korean Type




FIG 7: Argentinian Type




FIG 8: Japanese Type




AC Plug-US




AC Plug-EU




AC Plug-SA




AC Plug-UK




AC Plug-CH



AC Plug-KR



AC Plug-AR



AC Plug-JP

■ Safety agency approvals:



■ Specifications:

Model No.	GMPU40
AC input range	100~240VAC; 47~63Hz; 1.0~0.6A
Leakage current	0.1mA Max.@ 240VAC/50Hz
Operating temperature	-20°C to ~ +70°C (safety approval 0°C to 40°C, >40°C please contact the sales request derating curve.)
Withstand voltage	5656VDC from input to output
EMC	(A)CE:EN60601-1-2 (B)FCC Part 15 / Part 18 Subpart B
Safety	(A)UL/cUL (B)TUV/GS (C) TUV/PSE (D)CB(IEC60950-1)
Warranty	2 years

■ **X = UI:** (American type_FIG 1) or **EI:** (European type_FIG 2) or **SAI:** (2pin Australian type_FIG3) or **BSI:** (British type_FIG 4) or **CHI:** (Chinese type_FIG 5) or **KRI:** (Korean type_FIG 6) or **ARI:** (Argentinian type_FIG 7) or or **JPI:** (Japanese type_FIG 8)

Model name	Output Voltage(VDC)	Output Current(A)	Max.Output power(W)	Ripple.(mV) max.	Line Regulation(%)	Load Regulation(%)	Avg.Eff.(%) DoE (VI)_CoC (5)	No load Power Consumption(W)	Measured at the output of
GMPU40X-1	5~6	5.00~4.17	25	150	±1	±5	>84.30	<0.1	5
GMPU40X-1-1	6~8	5.00~3.75	30	150	±1	±5	>86.95	<0.1	7.5
GMPU40X-2	8~11	4.50~3.27	36	150	±1	±5	>87.60	<0.1	9
GMPU40X-3	11~13	3.63~3.07	40	150	±1	±3	>87.60	<0.1	12
GMPU40X-4	13~16	3.07~2.50	40	200	±1	±3	>87.60	<0.1	15
GMPU40X-5	16~21	2.50~1.90	40	200	±1	±3	>87.60	<0.1	18
GMPU40X-6	21~27	1.90~1.48	40	200	±1	±2	>87.60	<0.1	24
GMPU40X-7	27~33	1.48~1.21	40	300	±1	±2	>87.60	<0.1	28
GMPU40X-8	33~58	1.21~0.68	40	300	±1	±2	>87.60	<0.1	48

Note:

- 1.Weight: Approx 170~190gs
- 2.Optional output connectors (See appendix A)
- 3.Avg. Eff.(%): Averages the efficiency at 25, 50, 75, and 100% of max. rated output current.
- 4.Standard Output cable: **5~16V:** UL2468, 16AWG, 1M; **16~58V:** UL2468, 20AWG, 5FT