



E-Star Power Development Co., Ltd. (E-STAR)  
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City  
 22069, Taiwan (R.O.C.)  
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

**40W Wall Mount Power Supply < PA1045-HAB**

## FEATURES

**Over-Voltage Protection**  
**Over-Current Protection**

**Limit current Protection(Optional)**

**Short-circuit Protection**  
**100%Hi-pot & ATE(Chroma)Tested**

**100%Burn-in under High**  
**Ambient Temperature(45℃)**

**Low Ripple/Noise**  
**MTBF Above 50000 HRS At 25℃**

**LVD authentication**  
**Limited Power Sources(LPS)**

**CEC IV and V Efficiency**  
**Regulations Compliance**

**Cispr 22 CLASS B,VCCI CLASS B,**  
**FCC Part15 CLASS B, Compliance**

## Pa1045 HA Series Wall Mount 2PIN/Horizontal Type For AUSTRALIA



## SPECIFICATION

Item	Model No	PA1045-XHAB	PA1045-XHAB	PA1045-XHAB	PA1045-XHAB
	Part No	PA1045-120HAB~ PA1045-189HAB	PA1045-190HAB~ PA1045-240HAB	PA1045-241HAB~ PA1045-360HAB	PA1045-361HAB~ PA1045-480HAB
Output Voltage		12V~18.9V	19V~24V	24.1V~36V	36V~48V
Output Current(Max.)		3.33A	2.1A	1.66A	1.0A
Output Power(Max.)		40W	40W	40W	40W
Input Voltage		AC90~264V			
Input Frequency		47~63Hz			
Input Current		1.0A~1.5A Maximum			
Inrush Current		80A Maximum			
Line Regulation		1% Maximum			
Ripple&Noise		1% Maximum			
Load Regulation		5% Maximum			
Efficiency		≥ 86%			
Operating Temperature		0~40℃			
Storage Temperature		-20~85℃			
Over-Voltage Protection		Auto Recovery			
Short-circuit Protection		Auto Recovery			
Safety Standard		CB			
EMC(EMI/EMS)					

