






E-Star Power Development Co., Ltd. (E-STAR)
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City
 22069, Taiwan (R.O.C.)
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

6W Travel Power Supply > APSU06


UNIT:mm




AC Plug-US




AC Plug-EU




AC Plug-SA




AC Plug-UK




AC Plug-CH



AC Plug-KR



AC Plug-AR



AC Plug-JP

■ Safety agency approvals:



FC CE CB LPS

■ Specifications:

Model No.	APSU06
AC input range	100~240VAC; 47~63Hz; 0.2A
Leakage current	0.25mA Max.@ 240VAC/50Hz
Operating temperature	-20°C to ~ +70°C (safety approval 0°C to 40°C, >40°C please contact the sales request derating curve.)
Withstand voltage	4242VDC from input to output
EMC	(A)CE EN 55032, EN 55024 (B)FCC 47 CFR Part 15 Subpart B
Safety	(A) UL/cUL (B) TUV/GS (C) TUV/PSE (D) CB
Warranty	1 year

■ **X= UI:** (American type_FIG 1) or **EI:** (European type_FIG 2) or **SAI:** (2pin Australian type_FIG3) or **BSI:** (British type_FIG 4) or **CHI:** (Chinese type_FIG 5) or **KRI:** (Korean type_FIG 6) or **ARI:** (Argentinian type_FIG 7) or or **JPI:** (Japanese type_FIG 8)

Model name	Output Voltage(VDC)	Output Current(A)	Max.Output power(W)	Ripple.(mV) max.	Line Regulation(%)	Load Regulation(%)	Avg.Eff.(%) DoE(VI)_CoC(5)	No load Power Consumption(W)	Measured at the output of
APSU06X-0	3~5	1.33~0.80	4	50	±1	±7	>71.9	<0.1	3.3
APSU06X-1	5~6	1.20~0.80	6	50	±1	±5	>75.0	<0.1	5
APSU06X-1-1	6~8	1.00~0.75	6	80	±1	±5	>78.88	<0.1	7.5
APSU06X-2	8~11	0.75~0.54	6	80	±1	±5	>78.88	<0.1	9
APSU06X-3	11~13	0.54~0.46	6	100	±1	±3	>78.88	<0.1	12
APSU06X-4	13~16	0.46~0.37	6	120	±1	±3	>78.88	<0.1	15
APSU06X-5	16~21	0.37~0.28	6	150	±1	±3	>78.88	<0.1	18
APSU06X-6	21~27	0.28~0.20	6	180	±1	±2	>78.88	<0.1	24
APSU06X-7	27~33	0.20~0.18	6	200	±1	±2	>78.88	<0.1	28
APSU06X-8	33~58	0.18~0.12	6	200	±1	±2	>78.88	<0.1	48

Note:

- 1.Weight: Approx 70~100gs
- 2.Optional output connectors (See appendix A)
- 3.Avg. Eff.(%): Averages the efficiency at 25, 50, 75, and 100 % of max. rated output current.
- 4.Standard Output cable: **3~11V:** UL2468, 20AWG, 4FT ; **11~58V:** UL2468, 24AWG, 6FT