



12~15W Travel Power Supply < PS1010

Features

Over-Voltage Protection
 Over-Current Protection

Limit current Protection

Short-circuit Protection
 100%Hi-pot & ATE Tested

100%Burn-in under (40°C)

Low Ripple/Noise
 MTBF 50000 HRS At 25°C

LVD authentication
 Limited Power Sources(LPS)

DoE VI and CoC Tier VI Efficiency
 Regulations Compliance

Cispr 22 CLASS B, VCCI CLASS B,
 FCC Part15 CLASS B, Compliance

PS1010 Series

Wall Mount-Interchangeable-Side Plug In



Specification

Item	Model No	PS1010-xxxxxyzzz		
	Transformer	EE16-1	EE16-2	EE16-3
Output Voltage		3~7V	7.1~12V	12.1~15V
Output Current(Max.)		2.4A	1.0A	1.25A
Output Power(Max.)		12W	12W	15W
Input Voltage		AC90~264V		
Input Frequency		47~63Hz		
Input Current		0.4A Max		
Inrush Current		40A Max		
Line Regulation		1% Max		
Ripple&Noise		2% Max		
Load Regulation		5% Max		
Efficiency		DoE VI & CoC Tier 2 VI		
Operating Temperature		0~40°C		
Storage Temperature		-20~85°C		
Over-Voltage Protection		Auto Recovery		
Short-circuit Protection		Auto Recovery		
Safety Standard		CB		
EMC(EMI/EMS)				



E-Star Power Development Co., Ltd. (E-STAR)

1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City
22069, Taiwan (R.O.C.)

Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

12~15W Travel Power Supply < PS1010

機種編碼 Products code:

