



E-Star Power Development Co., Ltd. (E-STAR)
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City
 22069, Taiwan (R.O.C.)
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

15W Travel Power Supply > TRE15RD



Features

- * Universal Input Range 90~264Vac
 - * Meets EN55032 Class B and CISPR/FCC Class B
 - * Continuous Short Circuit Protection
 - * Over Voltage Protection
 - * No Load Power Consumption < 75mW
 - * Approved IEC/EN/UL 62368-1
 - * Meet CoC Tier 2 & DoE Level VI
 - * Class II
- (Output Cable Length \leq 1800mm)



Ordering Information

TRE15RDXX- XX	G	XX
Model No.	DC Plug Type	UL1571 WITH OVP DC Cable Length and Type
		01: 720mm
		02: 1220mm
		03: 1800mm
		11: 720mm with Ferrite
		12: 1220mm with Ferrite
		13: 1800mm with Ferrite
		* 20AWG for 5V, UL1571 or Equivalent
		* 18AWG for 9V, UL1571 or Equivalent
		* 24AWG for 12V, 15V, 24V, UL1571 or Equivalent

MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT	RIPPLE & NOISE NOTE 1	VOLTAGE ACCURACY NOTE 2	LINE REGULATION NOTE 3	LOAD REGULATION NOTE 4	AVERAGE EFFICENCY min. NOTE 5
TRE15RD050	5 V	2.0 A	50mVp-p	±2%	±1%	±4%	79.0%
TRE15RD090	9 V	1.4 A	90mVp-p	±2%	±1%	±2%	83.5%
TRE15RD120	12 V	1.0 A	100mVp-p	±2%	±1%	±2%	83.3%
TRE15RD150	15 V	1.0 A	100mVp-p	±2%	±1%	±2%	84.5%
TRE15RD240	24 V	0.63 A	100mVp-p	±2%	±1%	±2%	84.5%

Specifications are subject to change without notice.

